

Remarks on the conservation of mechanical energy in introductory mechanics

F C Santos ^{*}, V Soares [†] and A C Tort [‡]

Instituto de Física

Universidade Federal do Rio de Janeiro

Caixa Postal 68.528; CEP 21941-972 Rio de Janeiro, Brazil

February 2, 2008

Abstract

We discuss the work-kinetic energy theorem and the mechanical energy conservation theorem in the context of general physics courses. The motivation is the fact that all modern texts on introductory mechanics show the same conceptually dangerous statement that besides obliterating the concept of mechanical work, diminishing the importance of the work-kinetic energy theorem, leads to erroneous applications of the energy conservation theorem and at the same eliminates its relationship with the principle of the conservation of the mechanical momentum.

^{*}e-mail: filadelf@if.ufrj.br

[†]e-mail: vsoares@if.ufrj.br

[‡]e-mail: tort@if.ufrj.br.

1 Introduction: The work-kinetic energy theorem

Newton's laws of motion for a material point are at the very core of classical mechanics. Nevertheless, the application of those laws to more complex systems is not possible without the introduction of more encompassing concepts and general theorems. Here we will consider two of those theorems, namely, the work-kinetic energy theorem and the mechanical energy conservation theorem. The main motivation for this choice is the fact that almost all modern texts, see for example [1, 2, 3], on introductory mechanics show the same conceptually dangerous statement that besides obliterating the concept of mechanical work, diminishing the importance of the work-kinetic energy theorem, leads to erroneous applications of the energy conservation theorem and at the same eliminates its relationship with the principle of the conservation of the mechanical momentum. A system of particles is a set of arbitrarily chosen particles. It is important to stress that, once the system is chosen, no particle gets in or out of it, at least during the time interval, finite or infinitesimally small during which we observe it and apply to it the theorems of classical mechanics. It is convenient to divide the particles into two sets, the set of those that belong to the system under study and the set of those that do not belong to the system. The former are called internal particles and the latter external particles. The work-kinetic energy theorem states that the variation of the kinetic energy of a system of particles is equal to the total work performed by all forces acting on the system, the internal ones and the external ones. The principle of conservation of the mechanical energy follows from this theorem, therefore it is not a principle at all but a demonstrable corollary to it. However, in order to prove this corollary we must suppose that the system is isolated and that the internal forces are derivable from a scalar potential or do not perform mechanical work at all. It follows from this that standard problems such as the free fall, the frictionless sliding of a block on the surface of a wedge, the rolling without slipping of a sphere on an inclined plane, the gravitational catapult and many others cannot be solved with the (mis)use of the principle (corollary) of the conservation of the mechanical energy. The reason is very simple: the total mechanical energy of the system in these examples is not conserved. In what comes next we will strive to clarify this apparently bold statement.

2 Some simple examples

Consider a small block of mass m sliding without friction on the surface of a wedge with a mass M such that $M \gg m$. Let us analyse the problem initially from an inertial reference system $\mathcal{S}$ fixed to the wedge. The initial height of the small block is h and for the sake of simplicity we assume that the initial velocity is zero. The usual solution largely disseminated by the most popular textbooks on general physics [1, 2, 3] is based on the principle (corollary) of the conservation of mechanical energy. The reasons invoked for its application are: (i) there is no friction in the interface between the block and the wedge, (ii) the normal force (the constraint) does not perform work on the block. In this way, taking as a reference a point at the base of the wedge and recalling that the total energy is the sum of the potential energy and the kinetic one we obtain the following equation

$$mgh = \frac{1}{2}m\|\mathbf{v}\|^2, \quad (1)$$

where $\mathbf{v}$ is the velocity at the base of the wedge and parallel to it. Solving for $\|\mathbf{v}\|$ we obtain

$$\|\mathbf{v}\| = \sqrt{2gh}. \quad (2)$$

Consider now the same problem observed from a reference system $\mathcal{S}'$ moving with a constant velocity such that the velocity $\mathbf{V}$ of $\mathcal{S}$ with respect to $\mathcal{S}'$ is horizontal, i.e.: parallel to the base of the wedge.

Then the initial velocity of the small block is $\mathbf{V}$ and its final velocity is $\mathbf{v} + \mathbf{V}$. Therefore, the total initial energy of the block is

$$E_0 = \frac{1}{2}m\mathbf{V}^2 + mgh, \quad (3)$$

and the final energy is

$$E_1 = \frac{1}{2}m(\mathbf{v} + \mathbf{V})^2. \quad (4)$$

Therefore, the variation of the mechanical energy of the block is

$$\Delta E = m\mathbf{v} \cdot \mathbf{V}. \quad (5)$$

The last equation shows clearly that the total energy of the block in the reference system $\mathcal{S}'$ is not conserved and that there is no sense in talking about the conservation of the energy of the block with respect to the system $\mathcal{S}$ or any other reference system. This is so because for strong physical reasons *the principle must hold in any inertial reference system*. This point is clearly stressed at the introductory level only in Ref. [4], to the authors' knowledge. Here, the illusion of the conservation of the energy, according to Eq. (5), holds in the $\mathcal{S}$ reference system only. In this particular problem we find an additional complication, to wit, the system is not isolated since the wedge is on an horizontal plane. If we change the block by a rigid sphere that can roll down along the wedge without slipping we will find the same difficulties found in the sliding of the block. The fact that the friction forces do not perform work as textbooks usually state is no excuse for applying the conservation of energy. In these two examples, the impossibility of making use of the conservation of the energy becomes crystal clear if we take into account that in another inertial reference system the normal force and the friction force surely will do mechanical work.

Consider now an equally simple problem that can be viewed as an isolated system, but again the conservation of mechanical energy is erroneously applied to a part of the system only. Consider the free fall of a particle of mass m from a height h above the surface of the Earth and calculate its velocity immediately before it hits the ground. Most textbooks analyse the problem from the viewpoint of an inertial reference system $\mathcal{S}$ fixed with respect to the Earth and make use of the conservation of mechanical energy to obtain the final velocity, see for example [1, 2]. Besides, it is argued that since the Earth has a much larger mass than the particle it follows that its acceleration is negligible and therefore it can be considered as good approximation to a *bona fide* inertial reference system. The solution follows immediately from these assumptions. We write

$$mgh = \frac{1}{2}m\mathbf{v}^2, \quad (6)$$

and solve for $\|\mathbf{v}\|$. Consider the same problem from a reference system $\mathcal{S}'$ whose velocity with respect to the Earth is $\mathbf{V}$. The initial energy is given by

$$E_0 = \frac{1}{2}m\mathbf{V}^2 + mgh, \quad (7)$$

and the final energy is

$$E_1 = \frac{1}{2}m(\mathbf{v} - \mathbf{V})^2 + mg(-\mathbf{V}) \cdot \hat{\mathbf{k}}' \sqrt{\frac{2h}{g}}, \quad (8)$$

where we have taken into account the motion of surface of the Earth with respect to $\mathcal{S}'$ and the invariance of the elapsed time of free fall. The variation of mechanical energy is now given by

$$\Delta E = -m\mathbf{v} \cdot \mathbf{V} - mg\mathbf{V} \cdot \hat{\mathbf{k}}' \sqrt{\frac{2h}{g}}, \quad (9)$$

Once again conservation of the mechanical energy holds for one special reference system, the one in which the Earth is at rest.

3 The sliding block problem revisited

In the examples considered above it was shown that the mechanical energy is not conserved in an arbitrary inertial reference system if the mechanical system under study is not isolated. But our conclusion is based on the galilean rule for the transformation of velocities from one inertial system to another one. Our aim now is to show how a consistent application of the conservation laws of energy and momentum allow us to obtain the correct results. In order to do this we will simplify the problem and will keep only its essential features. We start by showing in a specific example that the conservation theorems correctly applied lead to the conclusion that the infinite mass of a part of the mechanical system is no excuse for disregarding energy and/or linear momentum transfer to it.

Consider again the problem of small block of mass m sliding down the inclined surface of a wedge of mass M . Choose an inertial system with respect to which the velocity of the wedge is always horizontal. Applying the theorems of the conservation of mechanical energy and linear momentum to the system constituted by the wedge *and* the small block we can write

$$\frac{1}{2} (M + m) \mathbf{V}_0^2 + mgh = \frac{1}{2} M \mathbf{V}^2 + \frac{1}{2} m (v_x^2 + v_y^2), \quad (10)$$

and

$$(M + m) V_0 = MV + mv_x, \quad (11)$$

where $\mathbf{V}_0$ is the initial velocity of the wedge, h is the initial height of the small block and v_x and v_y are the horizontal and the vertical components of its velocity at an arbitrary point. We have one more equation to write that reflects a kinematical constraint: the small block must never leave the inclined surface of the wedge, i.e.,

$$v_x - V = v_y \tan \theta, \quad (12)$$

where θ is the measure of the angle formed by the inclined surface of the wedge and the horizontal reference line. Equations (10) and (11) can be rewritten in the form

$$M (V - V_0) (V + V_0) - m (V_0 - v_x) (V_0 + v_x) + mv_y^2 - 2mgh = 0, \quad (13)$$

and

$$M (V - V_0) = m (V_0 - v_x). \quad (14)$$

Combining Eqs. (13) and (14) we obtain

$$m (V_0 - v_x) (V - v_x) + mv_y^2 - 2mgh = 0. \quad (15)$$

From Eq. (11) we have:

$$V = V_0 + \frac{m (V_0 - v_x)}{M}. \quad (16)$$

Taking this result into Eq. (12) we obtain

$$v_x - V_0 = \frac{M v_y \cot \theta}{M + m}. \quad (17)$$

If we now take this result together with Eq. (12) into Eq.(15) we can solve for v_y thus obtaining

$$v_y = \sqrt{\frac{2gh}{1 + \frac{M}{M+m} \cot^2 \theta}}. \quad (18)$$

Notice that when $\theta \rightarrow \pi/2$, the above formula gives $v_y \rightarrow \sqrt{2gh}$, and when $\theta \rightarrow 0$, $v_y \rightarrow 0$ as it must be. The determination of v_x and V follows easily

$$v_x = V_0 - \sqrt{\frac{2gh}{1 + \frac{M+m}{M} \tan^2 \theta}}, \quad (19)$$

and

$$V = V_0 + \frac{m}{M} \sqrt{\frac{2gh}{1 + \frac{M+m}{M} \tan^2 \theta}}. \quad (20)$$

Let us evaluate the variation of the energy and linear momentum of the wedge. The former is given by

$$\begin{aligned} \Delta E &= \frac{1}{2} M (V^2 - V_0^2) \\ &= \frac{m}{2} \sqrt{\frac{2gh}{1 + \frac{M+m}{M} \tan^2 \theta}} \left(2V_0 + \sqrt{\frac{2gh}{1 + \frac{M+m}{M} \tan^2 \theta}} \right), \end{aligned} \quad (21)$$

and the latter by

$$\begin{aligned} \Delta P &= M (V - V_0) \\ &= m \sqrt{\frac{2gh}{1 + \frac{M+m}{M} \tan^2 \theta}}. \end{aligned} \quad (22)$$

Finally we can analyse the behaviour of the system when the mass of the wedge goes to infinity. Taking the limit of $M \rightarrow \infty$ in Eqs. (21) and (22) we obtain

$$\lim_{M \rightarrow \infty} \Delta E = mV_0 \sqrt{2gh}, \quad (23)$$

and

$$\lim_{M \rightarrow \infty} \Delta P = m\sqrt{2gh}. \quad (24)$$

This example clearly shows how the principle of conservation of mechanical energy is misused. In the first place, Eq. (10), though correct, cannot be interpreted as conservation of energy because the system is not isolated, the external forces being supplied by gravity and contact forces. Equation (10) is a consequence of the work-kinetic energy theorem, which, in an obvious notation, reads for the system small block + wedge

$$W_g + W_{c.f.} = mgh = \Delta K_M + \Delta K_m. \quad (25)$$

In the second place, Eq. (23) shows that even in the infinite mass limit, or if one prefers, when $M \gg m$, there is energy transfer to the wedge.

4 Another example: The frontal collision problem

As a second example consider a block of mass M at rest with respect to the inertial reference system $\mathcal{S}$ and also a particle of mass m moving with a velocity $\mathbf{u}$ on a head-on collision course with the block. Suppose also that there is no external force acting on the parts of the system. In the end, of course, we will be interested in the particular, but important case where the mass of the block goes to infinity ($M \rightarrow \infty$). In this limiting situation, with respect to $\mathcal{S}$ the final velocity of the particle is $-\mathbf{u}$ and the final velocity of the block is still null. We will demonstrate that these results cannot be obtained with the application of the principle of the conservation of the energy only. Going from the inertial reference system $\mathcal{S}$ to $\mathcal{S}'$ with respect to which the velocity of the particle is $\mathbf{v}$ and the velocity of the block is $\mathbf{V}$ we write

$$MV + mv = MU + mu, \quad (26)$$

and

$$\frac{1}{2}MV^2 + \frac{1}{2}mv^2 = \frac{1}{2}MU^2 + \frac{1}{2}mu^2, \quad (27)$$

where U and u are the velocities of the block and of the particle respectively, after the collision. Solving for U and u we obtain

$$U = \frac{(2u - V)m + MV}{M + m}, \quad (28)$$

and

$$u = \frac{(m - M)v + 2MV}{M + m}. \quad (29)$$

The variations of the energy and linear momentum of the block are

$$\Delta E_M = \frac{M}{2} \left[\left(\frac{(2u - V)m + MV}{M + m} \right)^2 - \frac{1}{2}V^2 \right] \quad (30)$$

and

$$\Delta P_M = M \left[\frac{(2u - V)m + MV}{M + m} \right]. \quad (31)$$

respectively. Now take the limit $M \rightarrow \infty$ in the four equations above. The results are

$$U = V, \quad (32)$$

$$u = v + 2V, \quad (33)$$

and

$$\Delta E_M = 4mV(V - v), \quad (34)$$

$$\Delta P_M = 2(v - V)m. \quad (35)$$

Once again it is clear that the energy and the momentum of the block change even when its mass goes to infinity, or if we prefer, when $M \gg m$. However, in the special case where the initial velocity of the block is zero ($V = 0$), only its linear momentum changes.

5 Clarifying the matter

Consider the problem from a general point of view. Let a system of $N + M$ particles each with a mass m_i , $i = 1 \dots N + M$ be. Suppose that the system is isolated. Suppose also that the internal forces can be classified into two sets, namely: the set of conservative forces and the set of forces that do not perform work. Denoting by $\mathbf{x}_i$ the position and by $\mathbf{v}_i$ the velocity of particle of mass m_i , we write the total mechanical energy, the total linear momentum of the system, and the total angular momentum, respectively, as

$$E = \sum_{i=1}^{N+M} \frac{1}{2} m_i \mathbf{v}_i^2 + U(\mathbf{x}_i), \quad (36)$$

where $U(\mathbf{x}_i)$ is the total internal potential energy of the system, and

$$\mathbf{P} = \sum_{i=1}^{N+M} m_i \mathbf{v}_i \quad (37)$$

and

$$\mathbf{L} = \sum_{i=1}^{N+M} \mathbf{x}_i \times m_i \mathbf{v}_i. \quad (38)$$

Divide the system into two subsystems. The subsystem A formed by the $i = 1 \dots N$ particles and the subsystem B formed by the $N + 1 \dots N + M$ remaining particles. In this way the total mechanical energy given by Eq. (36), the total linear momentum given by Eq. (37) and the angular momentum can be decomposed in the following way

$$E = T_A + T_B + U_A + U_B + U_{AB}, \quad (39)$$

$$\mathbf{P} = \mathbf{P}_A + \mathbf{P}_B, \quad (40)$$

$$\mathbf{L} = \mathbf{L}_A + \mathbf{L}_B, \quad (41)$$

where $T_{A(B)}$ is kinetic energy of the system $A(B)$, $U_{A(B)}$ is the potential energy of $A(B)$, and U_{AB} is the interaction potential between the two subsystems. Recall that the complete system is isolated, therefore these mechanical quantities are conserved, that is

$$\frac{d}{dt} (T_A + U_A + U_{AB}) + \frac{d}{dt} (T_B + U_B) = 0, \quad (42)$$

$$\frac{d\mathbf{P}_A}{dt} + \frac{d\mathbf{P}_B}{dt} = 0, \quad (43)$$

$$\frac{d\mathbf{L}_A}{dt} + \frac{d\mathbf{L}_B}{dt} = 0. \quad (44)$$

Eq. (42) can be rewritten as

$$\frac{d}{dt} (T_A + U_A + U_{AB}) = -\frac{d}{dt} \left(\frac{1}{2} M_B \mathbf{V}_B^2 + T'_B \right) - \frac{dU_B}{dt}, \quad (45)$$

where M_B and $\mathbf{V}_B$ are the mass and centre of mass velocity of the subsystem B , respectively, and T'_B is its kinetic energy with respect to the centre of mass. In order to consider the subsystem B as an inertial

reference system suppose that the particles belonging to B are rigidly linked one to the other. This means that its internal potential energy is constant, $U_B = \text{constant}$, and the kinetic energy is given by

$$T'_B = \frac{1}{2} \omega_B \cdot \mathbf{I} \cdot \omega_B, \quad (46)$$

where we have introduced the angular velocity vector ω_B of the subsystem B and its inertia tensor. Expanding the rhs of Eq.(42) we obtain

$$\frac{d}{dt} (T_A + U_A + U_{AB}) = -\frac{d\mathbf{P}_B}{dt} \cdot \mathbf{V}_B - \frac{d\mathbf{L}_B}{dt} \cdot \omega_B. \quad (47)$$

Making use of Eqs. (43) and (44) we obtain

$$\frac{dE_{AB}}{dt} = \frac{d\mathbf{P}_A}{dt} \cdot \mathbf{V}_B + \frac{d\mathbf{L}_A}{dt} \cdot \omega_B, \quad (48)$$

where we have defined the mechanical energy of the subsystem A with respect to the subsystem B by

$$E_{AB} := T_A + U_A + U_{AB}. \quad (49)$$

In Eq. (48), the velocities $\mathbf{V}_B$ and ω_B depend both on time. let us analyse now what happens when the total mass of the rigid subsystem B goes to infinity. In this case after solving Eqs. (40) and (41) we obtain

$$\mathbf{V}_B = \frac{\mathbf{P} - \mathbf{P}_A}{M_B}, \quad (50)$$

and

$$\mathbf{I}_B \cdot \omega_B = \mathbf{L} - \mathbf{L}_A. \quad (51)$$

When we take infinite mass limit the total linear momentum $\mathbf{P}_A$ of the subsystem A remains constant, therefore we conclude that the velocity $\mathbf{V}_B$ and the angular velocity ω_B remain constant. The total energy of the subsystem hence is not conserved. Nevertheless, in the limit $M_B \rightarrow \infty$ and $\omega_B \rightarrow 0$, for which the velocity of M_B is zero and system B becomes an inertial system we have

$$\frac{dE_{AB}}{dt} = 0. \quad (52)$$

Equation (52) cannot be considered as a conservation law for the mechanical energy because it holds only in the inertial reference system for which the velocity of the subsystem B is zero. One must keep always in mind that a true conservation law must hold for all inertial reference system. Moreover, Eq. (49) that defines this energy contains the term U_{AB} that describes the interaction energy of the two systems, hence it cannot be interpreted as the total energy of the subsystem A .

References

- [1] Tipler A P 1999 *Physics for Scientists and Engineers*, 4th edn,(New York: Freeman)
- [2] Halliday D, Resnick R and Krane 1999 *Physics for Scientists and Engineers*, 5th edn (New York: Freeman)
- [3] Feynmann R P, Leighton R B and Sands M *The Feynmann Lectures on Physics Vol 1* (Reading: Addison-Wesley)
- [4] Kittel C, Knight W D and Ruderman M A 1970 *Berkeley Physics Course Vol. 1: Mechanics* (New York: McGraw-Hill)